



EZHD-TVF32 32 BNC Channel
+ 8 IP Bonus Channel Hybrid DVR

Key Features

- Triple Technology Recording: Connect 8 additional OMNI-IP Plug-and-Play or ONVIF cameras at up to 1080p resolution without sacrificing BNC inputs; configure up to 40 channels as 8 BNC + 8 IPC + mix match 24 more BNC and/or IP channels
- Intelligent Video Inputs: connect 1080p/720p EZHD HD-TVI or 960H/SD analog to ANY input at any time
 - Reuse existing analog cameras or choose any mix of HD/SD on new systems
 - Upgrade any analog camera to megapixel at any time
 - Superlative HD resolution of 1080p Full HD or 720p HD for amazing image quality
 - Useful digital zoom on live view and playback
 - Field select 1080p or 720p, 30/25 Hz or 60/50 Hz
 - Analog HD operation over 'almost any' wire
 - More than 1000 feet on standard RG59 coax
 - More than 1500 feet on RG6
 - More than 500 feet on UTP (one pair from a Cat5e cable, using optional KA-HDBAL1 balun pair).
- Display Live/Record 2.1 Megapixel 1920x1080 (1080p), 1 Megapixel 1280x960 (720p), 960x480 (WD1/960H), 704x480 (SD)
 - 1080p recording at up to 12FPS per camera
 - Real time recording on any/all channels at 720p, WD1 or SD resolution
 - Playback any/all cameras at up to record rate
 - Independent configuration for each channel: resolution main/sub-stream, FPS, bit rate, image quality, etc.
- Up-the-cable control [UTC] to access compatible camera OSD menus from the recorder's PTZ controls (local or remotely)
- H.264 Compression for efficient HDD utilization
 - Four internal hard drives for up to 16Tb of internal storage, plus eSATA port; HDD redundancy option
 - Up to 8 network disks (8 NAS disks, or 7 NAS disks + 1 IP SAN disk)
 - Simultaneous high bandwidth recording plus sub-stream recording for reduced bandwidth remote viewing
 - Watermarking for validation of recorded video
 - Record scheduling per-camera, with HDD quotas, holidays, parameter change on alarm/event
- Unique Channel 0 remote stream displays user defined multi-view in the bandwidth of a single channel
- Pentaplex Operation (Simultaneous live, recording, playback, archiving and remote viewing)
- Easy router setup for remote access: uPnP/NAT automatically sets up port forwarding (router must support/allow uPnP)
- HDMI/VGA and CVBS monitor outputs for up to 1080p HD display detail; use either for main or spot/call functions
- User friendly GUI with graphical icons, visual indicators and multiple language support
 - Easy to use on-screen menus include digital zoom and instant playback of recent video
- Operate using front panel controls, wheel mouse or included IR remote
- Quickly locate and review event video
 - Use Video Content Analysis event detection on one BNC channel
 - Line crossing (with direction) up to four lines
 - Area intrusion (with loitering time) up to four areas
 - Rapid fast forward can scan quickly between VCA events, yet plays events at normal speed
 - Use "Smart Search" to define an area of interest; the recorder quickly reviews recorded video to list instances of motion in that area for review by the operator
 - Search by date/time, or preview images by pointing along a color coded timeline of record type
 - Tag video of interest for easy retrieval or export
 - Play based on results of extensive event/alarm log search
- Digital Zoom with Virtual PTZ in Live & Playback
- Privacy masking (4 zones) to block observation of specific areas within the field of view
- Audio Inputs (5) and Outputs (1) for recording and/or two way audio
- Alarm Inputs (16) and Outputs (4) to interface with local hardware
- Ethernet gigabit interface for remote network viewing and control, and to connect IP cameras
- Multiple Control Inputs: local mouse/hand held IR remote controller (both included); web browser and CMS controls
- On-screen PTZ control via mouse or IR remote
- USB 2.0 ports on front and one on rear panel for video archive and mouse usage
- Free DDNS Service – static IP address is not required for reliable remote access
- IE, Chrome, Firefox and Safari browser Web clients
- Free Multi-Site Windows and MAC OMNI CMS can display up to 64 live/16 playback views
- Remote configuration support from built-in web interface and/or free OMNI CMS program
- Free iOS and Android apps:
 - Scroll through single/quad display live views
 - Playback specific cameras by date/time plus easy slider control
 - Audio monitoring support
 - PTZ and relay control
 - Up to 16 camera views from HD tablets (HD app)



EZHD-TVF32 32 BNC Channel + 8 IP Bonus Channel Hybrid DVR

8 Bonus IP Ch	40 Cameras Total	32 BNC Ports	Intelligent Ports	Replace up to 24 BNC with Streaming IP	ONVIF
1200 FPS	Real-Time 720p	Records up to 1080p	HDMI Main Monitor	VGA Main Monitor	eSATA
2 WAY AUDIO	5 Audio Inputs	Audio Output	H.264	Dual Stream Record	uPnP Router Setup
UTC Up The Cable OSD Control	E-MAIL NOTIFICATION	Digital Zoom	Water-marking	Remote Backup	Remote Preview
Smart Search	Bandwidth Optimization	Arming Schedule	Privacy Mask	Sub Stream	NAS SAN
VCA 1 Channel	Full Front Panel Controls	FREE CMS	FREE MAC Client	FREE APP IOS/Android	FREE DDNS
IR Remote Included	Jog Shuttle	Rack Mountable			

Intelligent Video Inputs	Analog EZHD/SD Inputs	32
	HD Video Resolutions	EZHD / HD-TVI 720p30(25), 720p60(50), 1080p30(25)
	Analog CVBS Video Input	Up to 960x480,720x480(NTSC); 960x576,720x576(PAL)
	Adaptive BNC Ports	Input Format Auto Detection, EZHD/SD can be mixed in any combination, at any time
	Interface	BNC Connector; 1V p-p, 75Ω
	Privacy masking	4 areas programmable in OSD menu
Video Output	Additional IP Channels (up to 2Mpixel)	8 (Omni IP Plug-and-Play or ONVIF)
	Total Cameras Supported	40 (8 IPC, 8 BNC, 24 mix/match between BNC & IPC; max 32 IPC plus 8 BNC or 32 BNC plus 8 IPC)
Recording	Main HDMI & VGA	Full HD 1920x1080/60Hz; SXGA: 1280x1024/60Hz; 720P: 1280x720/60Hz; XGA: 1024x768/60Hz
	Display Modes	1, 2x2, 1+5, 1+7, 3x3, 4x4, 5x5, 6x6 split per view; two predefined views, plus ad-hoc views. User Defined Sequence / Alarm Pop-up
Recording	Video Compression	Dual Stream: H.264 for Main Stream and Sub-stream
	Video Bitrate	32Kb/s-6Mb/s each channel
	Encoding	Main Stream: 1080p; 720p; WD1; 4CIF; VGA; CIF Sub Stream: WD1, 4CIF; CIF; QVGA; QCIF
	Frame Rate	Main Stream: 1/16 fps ~ Real time frame rate at 720p, to 12FPS at 1080p Sub Stream: 1/16 fps ~ Real time frame rate
	Quality	6 levels: Lowest/Lower/Low/Medium/Higher/Highest
	Mode	Continuous; Motion; Alarm; Motion or alarm, Motion + Alarm, VCA
	Motion and VCA Detection	Configurable per camera for area(s), sensitivity and arming schedule programmable by day of week and hour of day
	Schedule Period	Per day in 1 hour blocks; or 8 time periods per day, each with different record mode; plus holidays
	Pre/Post- Event Recording	Pre-record 0-30 seconds; post record 5s-10 minutes
	Playback	Synchronous Playback
Playback Resolution		1080p, 720p, WD1, 4CIF, VGA, CIF, QVGA, QCIF
Search Type		Time/Date; motion or log event; Manual Tags; Smart Search for motion events from recorded video
Capacity		Up to record rate
Playback Controls		Play; Pause; Forward/Reverse; speed control for single-1.8-16X; jog/shuttle Slide bar with overview of record type and snapshot display from slider position VCA based accelerated playback between normal play of VCA events
Digital Zoom During Playback		Supported on Local Displays and CMS
Event & Alarm	Event Source	MD (Motion Detection), Video Loss, Video Tampering/Exceptions; Video Content Analysis: Line Crossing with Direction (4 lines); Area Intrusion (4 areas) for one BNC channel.
	Event Action Schedule	Per day in 1 hour blocks; or 8 time periods per day, each with different record mode; plus holidays
	Event Action	Buzzer, E-mail, Alarm Full Screen Pop-up, Notify CMS Client, trigger alarm output
	MD Area	User selectable grid pattern 22x15 areas with adjustable per camera sensitivity
System Alarm	Alarm Source	HDD Error, HDD Full, LAN Fail/Address Conflict, Illegal login, Video Signal Exception/, Record/Capture exception
	Alarm Action	Buzzer, E-mail, Notify CMS Client (network permitting), trigger alarm output
Audio	Two-way audio	Audio input pass through to remote web or CMS client; remote audio from web or CMS client pass through to audio output
	Input	4 Inputs for record, 1 input for two way audio; RCA, 2V p-p, 1KΩ
	Output	1 Output; RCA, 2V p-p, 1KΩ
	Compression	Up to 64Kbps, G.711u
Network	Interface	10M/100M/1000M adaptive Ethernet RJ-45
	Addressing	Static IP, DHCP, xDSL support
	NTP/DST	Supported; choice of time zone, NTP server, DST start/end/offset
	Protocols Supported	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SMTP, SNMP, NFS, iSCSI, uPnP™, HTTPS, KT&C Plug-and-Play (for connected IP Cameras), OMNI Utility Device Discovery
	NAT	uPnP router NAT/port mapping forwards ports automatically (*Router must support/permit uPnP function)
	Users	Up to 128 simultaneous connected users
	DDNS	Simple DDNS free service tracks WAN IP address and HTTP port
	Security	User IDs
Security	User Levels	All rights for "admin"; Per camera per user rights assignment for Operator and User levels
	User Privilege Control	Local and remote access to Live views, audio, recording, playback, menus, PTZ, alarms, copy, logs, upgrade, reboot

Storage & Clip copy	HDD Storage	4 SATA HDD up to 4Tb each
	eSATA	One, on rear panel
	NAS/SAN	up to 8 network disks (8 NAS disks, or 7 NAS disks + 1 IP SAN disk)
	Copy Type	Multi-Channel or Single Channel File
	Copy Device	USB 2.0 Drive (2 ports) or eSATA
Serial & I/O	S.M.A.R.T.	Temperature, duration, error rates, bad sector detection, and more
	USB 2.0 Ports	Two front, one rear for mouse and data I/O
	Serial Port	1 RS-232C (future use)
	RS-485	One; selectable speed and bit pattern; multiple protocols (Pelco P, Pelco D, others)
	Inputs	16 alarm inputs
	Outputs	4 alarm outputs
User Controls	Keyboard	Input for external control keyboard
	Up the Cable Control	Multiple protocols, can be sent out of any BNC port to compatible cameras
Software	Local Controls	Front Panel camera, function and navigation buttons; IR Remote; Mouse
	Web Viewer	Live view, playback and configuration via IE, Chrome, Firefox, Safari (with free plug-in/extension installed)
General	User Rights Control	Per user-per camera for multiple functions
	Mobile Viewer	iOS and Android supported; live 1 & 4 camera views; single camera playback; snapshots from live or play; copy clips/record to smartphone; audio support; PTZ control. HD version of app, optimized for tablets, displays up to 16 live view cameras
	CMS	Free PC and MAC Clients support multiple device viewing, playback (with digital zoom) and configuration; user rights per camera; E-map support; live view up to 64 cameras in 4:3 and 48 cameras in 16:9; up to 16 cameras in playback
	Event Logging	Multiple types: alarm, exception, operation, information; dozens of sub-types within each major type
	Firmware Upgrade	From USB or remotely
	Backup/Restore Configuration	From USB or remotely
	Dimension (W x H x D)	17.5" x 15.3" x 2.7" 445 x 390 x 70mm
	Chassis Type	19" rack-mountable 1.5U chassis
	Weight without HDDs	11 lb. / 5Kg
	Operating Temp	14°F-131°F (-10°C-55°C)
Operating Humidity	10% ~ 90%	
Voltage	100-240 VAC 47-63Hz	
Power	Up to 65W	
Certifications	FCC, CE, RoHS	

Ordering Information:

EZHD-TVF32/2TB: 16 Ch, 2 TB | EZHD-TVF32/4TB: 16 Ch, 4 TB
EZHD-TVF32/8TB: 16 Ch, 8 TB | EZHD-TVF32/16TB: 16 Ch, 16 TB

www.ktncusa.com